



Model: **16-649P-** Item #: Date:
Project: Qty: Approved By:

Electronic Sensor Faucet Single Hole Deck Mount with 4-1/2" Gooseneck Spout

Royal Series



DESCRIPTION

- Battery Powered Electronic Sensor Faucet with Control Module, 4" Deck Plate, Spout Supply Hose & Mounting Hardware, Polished Chrome Finish, 4-1/2" Wide Gooseneck Spout

STANDARD FEATURES

- Single Hole Deck Mount
- Infrared Sensor Operated
- Battery Powered Control Module, (4) AA Batteries Included
- Built-In Filter to Prevent Debris from Entering Solenoid Valve
- Low Battery Indicator Light
- Battery Life 1-3 Years Based on Usage
- Warranty: 3 Years

SPECIFICATIONS

Water Inlet	1/4" Male NPS
Control Module Inlet (Mixing Valve)	1/2" Female NPS
Temp. Range	40°F - 180°F
Water Pressure	20-120 psi
Sensor Type	Infrared
Default Time Out	30 Seconds
Default Shut-Off Delay	1 Second
Default Auto Flush	Off
Sensor Range	3/4" - 8-1/4"
Battery Life	500,000 cycles
Material	Solid Brass
Finish	Polished Chrome
Weight	8 lbs.

OUTLETS

Standard Aerator	Suffix
<input type="checkbox"/> 0.50 GPM Aerator	E2
<input type="checkbox"/> 1.00 GPM Aerator	E3
<input type="checkbox"/> 1.50 GPM Aerator	E4
<input type="checkbox"/> 2.20 GPM Aerator	E6

Vandal Resistant Aerator	Suffix
<input type="checkbox"/> 0.50 GPM Aerator	G2
<input type="checkbox"/> 1.00 GPM Aerator	G3
<input type="checkbox"/> 1.50 GPM Aerator	G4

Laminar Flow Outlet	Suffix
<input type="checkbox"/> 0.50 GPM Outlet	F1
<input type="checkbox"/> 1.00 GPM Outlet	F2

Vandal Resistant Laminar Flow Outlet	Suffix
<input type="checkbox"/> 0.50 GPM Outlet	H2
<input type="checkbox"/> 1.00 GPM Outlet	H3
<input type="checkbox"/> 1.50 GPM Outlet	H4

Multi-Laminar Flow Outlet	Suffix
<input type="checkbox"/> 0.35 GPM Outlet	I2
<input type="checkbox"/> 0.50 GPM Outlet	I3
<input type="checkbox"/> 1.00 GPM Outlet	I4

Vandal Resistant Multi-Laminar Flow Outlet	Suffix
<input type="checkbox"/> 0.35 GPM Outlet	J1
<input type="checkbox"/> 0.50 GPM Outlet	J2

PRODUCT COMPLIANCE

- ASME A112.18.1-2011/CSA B125.1-11
- NSF-61
- NSF/ANSI 372
- Meets ANSI A117.1 (ADA)
- CEC Listed
- Massachusetts Approved



C US ADA Compliant

WARNING: Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes. California Proposition 65 Warning

Krowne Metal Corporation • 100 Haul Rd. Wayne, NJ 07470 • P: (800) 631-0442 • customerservice@krowne.com • krowne.com

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Rev. 01/2021 • No. 16-649P- _ _




Model: **16-649P-**__ Item #: _____ Date: _____
Project: _____ Qty: _____ Approved By: _____

Electronic Sensor Faucet Single Hole Deck Mount with 4-1/2" Gooseneck Spout

Royal Series

Replacement Parts

	Model	Description
1	16-506	Convex Sensor with Cable
2	16-511	Spout Supply Hose
3	16-198	Control Module
4	16-189	4" Deck Plate



Flow Control				Setting				
Shut-Off Delay	1s			10s		15s		
Auto Flush	ON				OFF			
Auto Time Out	15s	20s	25s	30s	45s	1m	2m	10m

Default Flow Control Setting Highlighted in Gray

