

| Project name: | | |
|---------------|------|--|
| Location: | | |
| Item: | Qty: | |
| Model: | | |

X-33 cleans your dishes and glassware.

This model is excellent for small restaurants, fast food operations, institutions, nursing homes, etc.













PERFORMANCE FEATURES

- Fully automatic washing and rinsing operation with integrated chemical injection system
- Wash tank heater to keep water warmer longer
- · Sanitary labyrinth door eliminates any gasket
- · Deep drawn one piece unified inner chamber
- · Rinse-additive pump for sparkling results
- · Detergent pump for consistent results
- · Chemical sanitizing pump
- · Just the push of one button fills the wash tank
- New and improved wash arm design
- · Highest quality fabrication using the most advanced machinery will ensure long-life and increased durability
- · Slide out control panel for ease of service and maintenance

TECHNICAL FEATURES

 Rack capacity: 37 racks per hour Complete operating cycle: 90 seconds Water consumption: 1.0 U.S. gallons

 Motor-pump: 0.75 H.P. Electrical: 115/60/1

• Amperage: 13.0 Amps / cord and plug included Water supply: 1/2" hot water supply 140°F (60°C)

• Flow Pressure: 25 PSI (dynamic) (PRV may be required)

 Water inlet connection: 3/4" male hose connector (hose included)

• Drain connection: 1" ID (25.4 mm) Max. height 36" (915 mm) (hose included)

Shipping weight: 178 lbs (81 kg)

OPTIONAL ACCESSORIES

· Pressure reducing valve (PRV) kit



3560 NW 56th Street Fort Lauderdale, FL, United States 33309 Telephone: 786.600.4687 / Toll Free: 844.218.8477 Fax: 786.661.4100

5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Telephone: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / Toll Free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com

JET-TECH is a registered trade mark of MVP Group. Specifications subject to change without notice. WARRANTY: 1 year parts and labor. Certain conditions apply. See Owner's Manual for details.

CONSTRUCTION FEATURES

- · Stainless steel pump impeller provides greater durability
- Standard insulated top and side panels
- · Stainless steel upper and lower wash/rinse arms are interchangeable and easily removed for cleaning
- · Body, external housing and all chasis components in brushed stainless steel AISI 304
- · Door safety switch
- Adjustable peristaltic pumps for detergent, rinse and sanitizer
- Door opening of 15"
- · Reliable mechanical type cam timer
- Detergent/chemical connections
- · Delime switch
- Cycle counter
- Automatic drain vavle mechanisme assists to drain water up
 to a height of 36"
- Standard equipment includes: One open combination rack of one peg dish rack 19.75" x 19.75" (500 mm x 500 mm)



