



MODELS

KGH-OF-(30, 40, 50, 60, 80, 100)-S

KGH-OF-(30, 40, 50, 60, 80, 100)-R

**GRAB-N-GO
HIGH PROFILE CASE**

CASE HOLDS 36°F TO 40°F • FORCED AIR REFRIGERATION • OPEN FRONT
FRONT LOADING • LED LIGHTING IN CANOPY AND UNDER SHELVES
PULL DOWN NIGHT CURTAIN • CASES CAN BE MULTIPLEXED



Intertek




Intertek



AUTODESK®
REVIT®

SELF CONTAINED	Model	Width (inches)	Capacity Cu.ft	Electrical				Nema Plug	Weight lbs		Crate Size (inches)		
				Compressor		Total Amps 115 V	Total Amps 230 V		No Crate	With Crate	L"	W"	H"
				H.P	F.L.A 115V								
	KGH-OF-30-S	29.2	15.9	3/4	16.0	20.7	N/A	Hard-wired	408	542	32.2	32.5	85.4
	KGH-OF-40-S	41	23.3	1	16.2	26.3	N/A	Hard-wired	463	633	44	32.5	85.4
	KGH-OF-50-S	50.2	29.1	1	16.2	27.0	N/A	Hard-wired	514	728	53.2	32.5	85.4
	KGH-OF-60-S	60.6	35.6	1-1/4	N/A	10.8	9.2	Hard-wired	580	818	63.6	32.5	85.4
	KGH-OF-80-S	78.2	46.6	2 x 1	N/A	11.2	16.4	Hard-wired	752	1049	81.2	32.5	85.4
	KGH-OF-100-S	96.6	58.2	2 x 1	2 x 16.2	2 x 27	N/A	Hard-wired	939	1285	99.6	32.5	85.4

REMOTE	Model	Width (inches)	115 Volts Total Amps	B.T.U	Nema Plug	Weight lbs	
						No Crate	With Crate
						KGH-OF-30-R	29.2
KGH-OF-40-R	41	0.90	6940	Hard-wired	353	523	
KGH-OF-50-R	50.2	1.30	7565	Hard-wired	404	617	
KGH-OF-60-R	60.6	1.36	9383	Hard-wired	463	701	
KGH-OF-80-R	78.2	1.81	13881	Hard-wired	562	860	
KGH-OF-100-R	96.6	2.60	14921	Hard-wired	691	1043	



STANDARD FEATURES

- Tempered side glass
 - Pull down night curtain
 - CFC free injected foam insulation
 - Silver colored PVC coated steel front panel
 - PVC coated steel gray interior
 - Black steel kick plate
 - Foamed polystyrene black end panels
 - Height adjustable shelves can be tilted
 - Products stop on all shelves
 - Temperature and defrost regulated by a digital controller
 - Removable condensate evaporating pan for easy cleaning on self contained units
 - Slide out condensing unit on self-contained units
 - Digital thermometer
 - Levelling feet
- ### OPTIONAL FEATURES
- Stainless steel interior and / or exterior
 - Other colors available
 - Solid or full view end panels
 - Additional shelves
 - Joining Kit
 - Partition and or / product dividers
 - Price tag molding
 - Condensate evaporating pan for remote cases
 - Casters add 4-3/8" to height
 - Stainless steel legs are adjustable from 5-1/8" to 7-5/8"

Standard Mounting



Levelling Feet

Optional Mounting



Adjustable Legs



Casters

NOTE

These cases are engineered to operate in locations not exceeding 75°F and 55% R.H. These cases are designed to operate using R404a refrigerant. Alternate refrigerants available by special order. O.A. length includes (2) ends at 1-1/2" each. Ventilation grills at front and back cannot be blocked. B.T.U's are calculated at 14°F (evaporator) and 90°F (ambient). Remote cases are provided with an expansion valve and a liquid solenoid for pump down cycle. On remote cases, if no floor drain is provided, a condensate evaporating pan must be ordered and 3.3 or 8.3 amps added to the amp load. Remote cases must be hard wired – no plugs.

WARRANTY

One year parts and labor with an additional four years on the compressor (part only)

Tel: 786.600.4687 / Toll Free: 844.218.8477
Fax: 786.661.4100

Tel: 514.737.9701 / Toll Free: 888.275.4538
Fax: 514.342.3854 / toll free: 877.453.8832

