

DMR DOME RACKS & BSR INDUCTION BASE RACKS





Model	Number of	Capacity of	Overall Dimensions							Caster		Shipping	
Number			Height		Depth		Width		Diameter		Weight		l
	Shelves	Domes/Underliners	in	mm	in	mm	in	mm	in	mm	lbs	kg	
DMR50	5	50/100	733/8	1863	193/4	502	22	559	5	127	76	34	1
DMR80	4	80/160	$60^{3/8}$	1533	$19^{3/4}$	502	40	1016	5	127	71	32	l
DMR100	5	100/200	$73^{3/8}$	1863	$19^{3/4}$	502	40	1016	5	127	98	44	

Model		Capacity of			Overall D	imensio	Ca	Caster		Shipping		
Number			Height		Depth		Width		Diameter		Weight	
	Shelves	Induction Bases	in	mm	in	mm	in	mm	in	mm	lbs	kg
BSR90	5	50/100	691/2	1765	19 ³ / ₄	502	22	559	5	127	81	37
BSR180	5	80/160	69 ¹ / ₂	1765	$19^{3/4}$	502	40	1016	5	127	108	49
BSR270	5	100/200	691/2	1765	19 ³ / ₄	502	58	1473	5	127	130	59

CONSTRUCTION...Completely welded straight line modular construction. All horizontal supports are welded and polished to vertical uprights to form one-piece rigid cart. Extra welds on bottom supports for maximum support and added durability.

MATERIAL...All stainless steel construction; Framework and supports constructed of 1" x 18 gauge seamless, polished stainless steel tubing.

CASTERS...Stem mounted 5" diameter red Performa casters. All full ball bearing swivel. Two fitted with brakes.

CRADLES...Each shelf contains cradles that are easily removable for cleaning and direct dishwasher use. All cradles are constructed of 5/16" diameter stainless steel wire. DMR cradle capacity: 10 domes or 20 underliners per base. BSR cradle capacity: 10 induction bases per cradle.

CRADLE SUPPORTS... stainless steel angle type supports heli-arc welded to vertical uprights.

OPTIONS & ACCESSORIES...

☐Additional wire cradle (DMR) ☐Additional wire cradle (BSR)

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN

1551 McCormick Ave., Mundelein, IL 60060 (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981 www.carter-hoffmann.com

